

9225C DC axial flow fan

9225C DC Axial Flow Fan —92.0×92.0×25.0 mm

★ Structural Features

Frame & Blade Material


- Frame: Aluminum Alloy
- Impeller: Engineering Plastic

Bearing Structure: Dual Ball Bearings


Weight: 145.0 g



★ Mechanical Dimensions



★ Airflow Performance Curve



Basic Fan Specifications

Model	Voltage (V)	Operating Voltage Range (V)	Power (W)	Speed (RPM)	Airflow (m³/h)	Static Pressure (Pa)	Noise (dBA)	Curve
J92FZW140-25C00	12	8.0~13.8	3.84	4000	108.6	67.0	44.5	①
J92FZW155-25C00	12	8.0~13.8	10.8	5500	149.3	126.7	51.4	②
J92FZW240-25C00	24	16.0~27.6	3.84	4000	108.6	67.0	44.5	①
J92FZW255-25C00	24	16.0~27.6	10.8	5500	149.3	126.7	51.4	②
92FZW340-25C00	28	18.0~32.0	3.84	4000	108.6	67.0	44.5	①
J92FZW355-25C00	28	18.0~32.0	10.8	5500	149.3	126.7	51.4	②

Notes:

- In the model number, the **second digit from the end “0”** indicates the **signal function**, and the **last digit “0”** indicates the **environmental performance rating**.
- Users may select according to actual requirements based on **Table 1** and **Table 2**.
- Available voltage options: **5V, 12V, 24V, 28V, 48V**

Table 1: Signal Functions

Signal function code	0	1	2	3	4	5
Function Description	No Function	PWM Duty Cycle Speed Control	High-Level Fault Alarm	Tachometer (RPM) Feedback	PWM Duty Cycle Control + High-Level Fault Alarm	PWM Duty Cycle Control + Tachometer Feedback

Table 2: Environmental Adaptability Ratings

Code	Application Standard	0 (Ground Vehicle-Mounted)	1 (Marine / Naval Applications)	2 (Airborne Applications)	
High Temperature	GJB150.3A-2009	Storage: 80°C, Operation: 75°C		Storage: 95°C, Operation: 85°C	
Low Temperature	GJB150.4A-2009	Storage: -50°C, Operation: -40°C		Storage: -60°C, Operation: -55°C	
Rain / Water Ingress	GJB150.8A-2009	Enhanced, 1 hour per surface			
Damp Heat (Humidity)	GJB150.9A-2009	Cyclic humidity: 30°C-60°C, RH 95%±5%, 24h per cycle, 10 cycles			
Fungus Resistance	GJB150.10A-2009	Fungus group 1 or group 2, 28 days			
Salt Spray	GJB150.11A-2009	Neutral salt spray 192 hours	Acidic Salt Spray, 192 hours		
Sand & Dust	GJB150.12A-2009	Blowing sand and dust test			
Acceleration	GJB150.15A-2009	Three-axis, six-direction; Performance test level: 9g, Structural test level: 13.5g			
Shock	GJB150.18A-2009	Three-axis, six-direction, 18 shocks total, 20g		Three-axis, six-direction, 18 shocks total, 30g	
Low Air Pressure	GJB150.2A-2009	/		6.3kPa	
Acidic Atmosphere	GJB150.28A-2009	/		Spray 2h + storage 22h per cycle, 3 cycles	
EMC (Electromagnetic Compatibility)	GJB151B-2013	Comply with RE102 and CE102			
Power Supply Characteristics	GJB181B-2012	/		Abnormal Overvoltage 50V/50ms	
Vibration	GJB150.16A-2009	