

# 12725A DC Blower Fan

12725A DC Blower Fan — 127.0 × 127.0 × 25.4 mm


## ★ Structural Features

### Frame & Blade Material


- Frame: Aluminum alloy
- Impeller: Engineering Plastic

Bearing Structure: Dual Ball Bearings


Weight: 360.0 g



## ★ Mechanical Dimensions



## ★ Airflow Performance Curve



## Basic Fan Specifications

Model	Voltage (V)	Operating Voltage Range (V)	Power (W)	Speed (RPM)	Airflow (m³/h)	Static Pressure (Pa)	Noise (dBA)	Curve
J127FLW151-25A00	12	8.0~13.8	8.0	5100	64.0	405.1	63.4	①
J127FLW164-25A00	12	8.0~13.8	18.6	6400	80.7	637.6	68.3	②
J127FLW251-25A00	24	16.0~27.6	8.0	5100	64.0	405.1	63.4	①
J127FLW264-25A00	24	16.0~27.6	18.6	6400	80.7	637.6	68.3	②
J127FLW351-25A00	28	18.0~32.0	8.0	5100	64.0	405.1	63.4	①
J127FLW364-25A00	28	18.0~32.0	18.6	6400	80.7	637.6	68.3	②

- **Notes:** Available voltage options: **5V, 12V, 24V, 28V, 48V**
- In the model number, the **second digit from the end “0”** indicates the **signal function**, and the **last digit “0”** indicates the **environmental performance rating**.
- Users may select according to actual requirements based on **Table 1** and **Table 2**.

**Table 1: Signal Functions**

Signal function code	0	1	2	3	4	5
Function Description	No Function	PWM Duty Cycle Speed Control	High-Level Fault Alarm	Tachometer (RPM) Feedback	PWM Duty Cycle Control + High-Level Fault Alarm	PWM Duty Cycle Control + Tachometer Feedback

**Table 2: Environmental Adaptability Ratings**

Code	Application Standard	0 (Ground Vehicle-Mounted)	1 (Marine / Naval Applications)	2 (Airborne Applications)	
High Temperature	GJB150.3A-2009	Storage: 80°C, Operation: 75°C		Storage: 95°C, Operation: 85°C	
Low Temperature	GJB150.4A-2009	Storage: -50°C, Operation: -40°C		Storage: -60°C, Operation: -55°C	
Rain / Water Ingress	GJB150.8A-2009	Enhanced, 1 hour per surface			
Damp Heat (Humidity)	GJB150.9A-2009	Cyclic humidity: 30°C-60°C, RH 95%±5%, 24h per cycle, 10 cycles			
Fungus Resistance	GJB150.10A-2009	Fungus group 1 or group 2, 28 days			
Salt Spray	GJB150.11A-2009	Neutral salt spray 192 hours	Acidic Salt Spray, 192 hours		
Sand & Dust	GJB150.12A-2009	Blowing sand and dust test			
Acceleration	GJB150.15A-2009	Three-axis, six-direction; Performance test level: 9g, Structural test level: 13.5g			
Shock	GJB150.18A-2009	Three-axis, six-direction, 18 shocks total, 20g		Three-axis, six-direction, 18 shocks total, 30g	
Low Air Pressure	GJB150.2A-2009	/		6.3kPa	
Acidic Atmosphere	GJB150.28A-2009	/		Spray 2h + storage 22h per cycle, <b>3 cycles</b>	
EMC (Electromagnetic Compatibility)	GJB151B-2013	Comply with RE102 and CE102			
Power Supply Characteristics	GJB181B-2012	/		Abnormal Overvoltage 50V/50ms	
Vibration	GJB150.16A-2009	